



US005982407A

United States Patent [19]

Enomoto et al.

[11] **Patent Number:** 5,982,407[45] **Date of Patent:** *Nov. 9, 1999[54] **COLOR PRINTER**[75] **Inventors:** Jun Enomoto; Hiroaki Nakamura,
both of Kanagawa, Japan[73] **Assignee:** Fuji Photo Film Co., Ltd., Kanagawa,
Japan[*] **Notice:** This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).[21] **Appl. No.:** 08/763,721[22] **Filed:** Dec. 11, 1996[30] **Foreign Application Priority Data**

Dec. 13, 1995 [JP] Japan 7-324657

[51] **Int. Cl.⁶** B41J 2/47[52] **U.S. Cl.** 347/239; 347/252[58] **Field of Search** 347/239, 238,
347/252, 232[56] **References Cited****U.S. PATENT DOCUMENTS**

5,028,939	7/1991	Hornbeck et al.	347/131
5,296,958	3/1994	Roddy et al.	347/232 X
5,337,074	8/1994	Thornton	347/238 X
5,657,071	8/1997	Shinohara	347/252

OTHER PUBLICATIONS

N. Nishida: "Micro machines and optical techniques (2), Digital micromirror devices (DMD) and their applications to

displays", O plus (a magazine), Oct. 1994, No. 179, pp. 90-94.

G. Foley et al.: "S7-6 Recent Advances in Actuated Mirror Array (AMA) Projector Development"; Aura Syss., Inc. El Segundo, USA. Daewoo Elect., Seoul, Korea, 1995.

"Mirrors on a Chip"; IEEE Spectrum, Nov. 1993; pp. 27-31.

"Digital Micromirror Device Imaging Bar for Hardcopy";

Nelson et al.; Digital Imaging Venture Project Texas Instruments Inc., P.O. Box 655474. M/S 440, Dallas, Texas

75265-5474; SPIE vol. 2413; pp. 58-65, Feb. 1995.

"Micromirrors and Digital Processing"; Photonics Spectra;

May 1995; pp. 118-124.

Primary Examiner—N. Le*Assistant Examiner*—Lamson D. Nguyen*Attorney, Agent, or Firm*—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57]

ABSTRACT

A color printer is equipped with a digital micromirror device having at least one micromirror array constituted of a number of micromirrors. Each micromirror changes its tilt angle in accordance with a value of mirror drive data of one bit. As the mirror drive data takes a value "1", the micromirror reflects spot light toward color paper, whereas as the mirror drive data takes a value "0", it reflects spot light toward a light absorption plate. During red exposure, red light from a red LED unit is incident upon the digital micromirror device which is then driven by red mirror drive data to expose a red image on the color paper. Next, during radiation of a green LED unit, the digital micromirror device is driven by green mirror drive data to expose a green image on the color paper. Lastly, a blue image is exposed on the color paper by using a blue LED unit. A full-color image is therefore printed on the color paper through three-color line- or frame-sequential exposure.

20 Claims, 7 Drawing Sheets